

Available from now on



NEW!



Grünin  Loske
www.gruelo.de

- Designed to operate 4x longer before requiring maintenance
- Latest seal technology effectively handles dirty or recycled water for improved performance
- Streamlined design keeps tool from catching inside pipe
- Individually replaceable fins made of hardened steel for 4x longer life
- Choose your rotation speed with 3 viscous fluid options: rear jetting, descaling and **SWITCHER**™
- Carbide nozzles of highest quality
- Independently replaceable fins can be easily replaced as wear occurs without opening tool body



	WGR-1 1/4	WGR-1	WHR-3/4	WHR-1/2
PRESSURE	Up to 5000 psi (350 bar)	Up to 5000 psi (350 bar)	Up to 8000 psi (550 bar)	Up to 8000 psi (550 bar)
FLOW	80-120 gpm (300-455 l/min)	50-80 gpm (190-300 l/min)	16-50 gpm (60-190 l/min)	14-25 gpm (53-95 l/min)
PIPE SIZE	8-36 in. (200-900 mm)	8-36 in. (200-900 mm)	6-18 in. (150-450 mm)	6-18 in. (150-450 mm)
INLET	1 ¼ NPT/BSPP	1 NPT/BSPP	¾ NPT/BSPP	½ NPT/BSPP